

Version number 302

Revision: 09.10.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Gun-applied foam E-COLL

- · Article number: 4317784150903, 4317784150910
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) • Application of the substance / the mixture Sealant
- \cdot 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 *e-mail: sdb@ede.de*

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

GHS08 health hazard

Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2	H351	Suspected of causing cancer.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335	May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. • *Hazard pictograms*



(Contd. on page 2)

⁻ GB



Version number 302

Revision: 09.10.2015

Trade name: Gun-applied foam E-COLL

Signal w	ord Danger (Contd. of page	1)
U	determining components of labelling:	
	methanediisocyanate, isomeres and homologues	
	tatements	
-	229 Extremely flammable aerosol. Pressurised container: May burst if heated.	
H332	Harmful if inhaled.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H317	May cause an allergic skin reaction.	
H351	Suspected of causing cancer.	
H335	May cause respiratory irritation.	
H373	May cause damage to organs through prolonged or repeated exposure.	
Precautio	onary statements	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking	<u>z</u> .
P251	Do not pierce or burn, even after use.	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P211	Do not spray on an open flame or other ignition source.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P309+P3	311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.	
	412 Protect from sunlight. Do not expose to temperatures exceeding 50 $^{\circ}C/122$ $^{\circ}F$.	
P501	Dispose of contents/container in accordance with local/regional/national/internation regulations.	al
Addition	al information:	
suffering product.	already sensitised to isocyanates may develop allergic reactions when using this product. Perso from asthma, eczema or skin problems should avoid contact, including dermal contact, with the This product should not be used under conditions of poor ventilation unless a protective mask with priate gas filter (i.e. type A).	his
	isocyanates. May produce an allergic reaction.	
	r hazards	
	f PBT and vPvB assessment	
	t applicable.	
	ot applicable.	

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	25-50%
	 Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 	
CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate	10-25%
Reg.nr.: 01-2119447716-31-xxxx	(1) Acute Tox. 4, H302	
CAS: 74-98-6	propane	2,5-10%
EINECS: 200-827-9	Flam. Gas 1, H220; Press. Gas C, H280	
Reg.nr.: 01-2119486944-21-xxxx		

GB —



Version number 302

Revision: 09.10.2015

Trade name: Gun-applied foam E-COLL

	(Cor	td. of page 2)
CAS: 75-28-5	isobutane	2,5-10%
EINECS: 200-857-2	🛞 Flam. Gas 1, H220; Press. Gas C, H280	
Reg.nr.: 01-2119485395-27-xxxx		
CAS: 115-10-6	dimethyl ether	2,5-10%
EINECS: 204-065-8	🛞 Flam. Gas 1, H220; Press. Gas C, H280	
Reg.nr.: 01-2119472128-37-xxxx		

• Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information:
- Personal protection for the First Aider.
- Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air.
- Seek medical treatment in case of complaints.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing:
- *Rinse out mouth and then drink plenty of water. Seek immediate medical advice.*
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- \cdot Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment:
- Do not inhale explosion gases or combustion gases. Mouth respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray. Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

⁻ GB



Version number 302

(Contd. of page 3)

Trade name: Gun-applied foam E-COLL

· 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle receptacle with care. Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Keep container tightly sealed.

Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m³ Long-term value: 0,02 mg/m³ Sen; as -NCO

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

· DNELs

13674-84-5 tris(2-chlorisopropyl)-phosphate

Dermal Long term value for employees 0.528 mg/kg bw/Tag (-)

Inhalative Long term value for employees $0.93 \text{ mg/m}^3(-)$

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

• General protective and hygienic measures:

Wash hands before breaks and at the end of work.



Version number 302

Revision: 09.10.2015

Trade name: Gun-applied foam E-COLL

not inhale gases / fumes / aerosols. oid contact with the skin. oid contact with the eyes. spiratory protection: e suitable respiratory protective device in case of insufficient ventilation. ort term filter device: ter A/P2 otection of hands:	
oid contact with the eyes. spiratory protection: e suitable respiratory protective device in case of insufficient ventilation. fort term filter device: ter A/P2 ptection of hands:	
spiratory protection: e suitable respiratory protective device in case of insufficient ventilation. ort term filter device: ter A/P2 otection of hands:	
e suitable respiratory protective device in case of insufficient ventilation. ort term filter device: ter A/P2 otection of hands:	
ort term filter device: ter A/P2 otection of hands:	
ter A/P2 otection of hands:	
otection of hands:	
Protective gloves	
rile rubber, NBR	
commended thickness of the material: ≥ 0.4 mm	
netration time of glove material	
e exact break through time has to be found out by the manufacturer of the protective glov	es and has to be
served.	
e protection:	

· Body protection: Impervious protective clothing

9.1 Information on basic physical a General Information Appearance:	nd chemical properties	
Form:	Aerosol	
Colour:	Different according to colouring	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Not applicable, as aerosol.	
Flash point:	Not applicable, as aerosol.	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	235 °C	
Decomposition temperature:	Not determined.	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidising properties	Not determined.	
Vapour pressure at 20 °C:	5200 hPa	



Version number 302

Revision: 09.10.2015

Trade name: Gun-applied foam E-COLL

		(Contd. of page 5
· Density at 20 •C:	0,9 g/cm ³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solids content:	30,0 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- \cdot 10.4 Conditions to avoid No further relevant information available.
- $\cdot \ 10.5 \ Incompatible \ materials: \ No \ further \ relevant \ information \ available.$
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity
- Harmful if inhaled.
- · LD/LC50 values relevant for classification:

13674-84-5 tris(2-chlorisopropyl)-phosphate

Oral LD50 3600 mg/kg (rat)

· Primary irritant effect:

- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity
- Suspected of causing cancer.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause respiratory irritation.
- · STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)



Version number 302

Revision: 09.10.2015

Trade name: Gun-applied foam E-COLL

(Contd. of page 6)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

15 01 10* packaging containing residues of or contaminated by dangerous substances

· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
ADR	UN1950 AEROSOLS	
· IMDG, IATA	AEROSOLS	
· 14.3 Transport hazard class(es)		
ADR		
· Class	2 5F Gases.	
· Label	2.1	
· IMDG, IATA		
	2 Gases.	



Version number 302

Trade name: Gun-applied foam E-COLL

	(Contd. of page
· 14.4 Packing group · ADR	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· 14.7 Transport in bulk according to Ann Marpol and the IBC Code	nex II of Not applicable.
· Transport/Additional information:	
·ADR	
· Limited quantities (LQ)	1L
· Transport category	2
• Tunnel restriction code	D
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Information about limitation of use:
- Employment restrictions concerning pregnant and lactating women must be observed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure. · Department issuing MSDS: Product safety department · Contact: Head of Product Safety Department · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 9)



Version number 302

Revision: 09.10.2015

Trade name: Gun-applied foam E-COLL

	(Contd. of page 8)
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
DNEL: Derived No-Effect Level (REACH)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1: Flammable gases, Hazard Category 1	
Aerosol 1: Flammable aerosols, Hazard Category 1	
Press. Gas C: Gases under pressure: Compressed gas	
Acute Tox. 4: Acute toxicity, Hazard Category 4	
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2	
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1	
Skin Sens. 1: Sensitisation - Skin, Hazard Category I	
Carc. 2: Carcinogenicity, Hazard Category 2	
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3	
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2	GB